

PRODUCT DATA SHEET

ADNOC Supreme 2T

DESCRIPTION

ADNOC Supreme 2T is a semi-synthetic two-cycle oil formulated from a special blend of mineral and synthetic oil and low-ash additive package to release maximum power with minimum drag.

APPLICATIONS

ADNOC Supreme 2T is recommended for high performance, motorcycles, especially for road use. It is also recommended for smaller engine fitted in scooters, lawn mowers and other small equipment. It should be added with gasoline in the ratio recommended by the equipment manufacturer.

BENEFITS

- Superior combustion characteristics of the special blend of Semi-Synthetic and highly refined mineral oils and additives, significantly reduce visible smoke in exhaust emission. Providing environmental friendly lubricants
- Controls Combustion Chamber and Spark Plug deposit build-up
- Excellent miscibility with gasoline
- Keeps pistons, rings, plugs and exhaust ports clean

PERFORMANCE LEVEL

JASO FD
API TC

ISO EGD

PRODUCT TYPICAL CHARACTERISTICS

Properties	Units	Typical	Test Methods
Density @15°C	kg/L	0.872	ASTM D1298
Kinematic Viscosity @100°C	mm ² /s	9.000	ASTM D445
Pour Point	°C	-30	ASTM D97
Flash Point, PMCC	°C	70	ASTM D93

Minor variations in product typical test data are to be expected in normal manufacturing.

Always follow the Original Equipment Manufacturer's recommendation (OEM) for the equipment operating conditions, product specification, drain interval and customer's maintenance practices.

Rev: 12-Aug-2022