



PRODUCT DATA SHEET

ADNOC OGL & WR Compound

DESCRIPTION

ADNOC OGL & WR Compound is a bituminous base compound containing diluents primarily for Open Gear and Wire Rope lubrication. It has a wide range of usable temperature. It is recommended for Open Gears which work under load, where it forms a strong tenacious film on the metal surface which does not get squeezed out during usage. It has good penetration properties to lubricate between strands of wire ropes. This product can be applied by brushing, swabbing, dipping and spraying. Product is supplied in diluted form.

APPLICATIONS

ADNOC OGL & WR Compound is recommended for use in Open Gear Lubrication and Wire Rope Lubrication. Can also be used in Chain and Sprocket systems where bituminous compounds are recommended.

PRODUCT TYPICAL CHARACTERISTICS

Properties	Units	Typical	Test Methods
Appearance	Visual	Black	-
Density @15°C	kg/L	0.980 - 1.000	ASTM D1298
Kinematic Viscosity @25°C, Diluted	mm ² /s	500 - 600	ASTM D445
Kinematic Viscosity @100°C, Undiluted	mm ² /s	420 - 480	ASTM D445
Flash Point, COC	°C	< 55	ASTM D92

Minor variations in product typical test data are to be expected in normal manufacturing.

Always follow the Original Equipment Manufacturer's recommendation (OEM) for the equipment operating conditions, product specification, drain interval and customer's maintenance practices.

Rev: 11-Nov-2022