

# PRODUCT DATA SHEET

## ADNOC MOULD OIL KW

### DESCRIPTION

**ADNOC MOULD OIL KW** is an effective mold release compounds for cast concrete products. Formulated from highly refined mineral oils, it produces a high quality concrete finish resisting blowholes and providing uniform surface finish.

### APPLICATIONS

- Ready to use packs – no dilution required.
- Manual fine hair brush application or spray application through fine mist.
- Spray application should only be with a nozzle giving a fine mist.
- Over application may result in surface retardation.

### BENEFITS

- Excellent performance in the prefabrication of aerated concrete with metal forms.
- High coverage, Water repellent; rust prevention.

### PRODUCT TYPICAL CHARACTERISTICS

Properties	Units	ADNOC MOULD OIL KW	Test Method
Colour		L5.0	ASTM D 1500
Density @ 29.5 oC	kg/L	0.892	ASTM D1298
Kinematic Viscosity @ 40oC	mm <sup>2</sup> /s	155-165	ASTM D445
Kinematic Viscosity @ 100oC	mm <sup>2</sup> /s	14.5	ASTM D445
Viscosity Index	-	Min 85	ASTM D2270
Total Acid Number mg	KOH/gm	Min 3.0	ASTM D 664

Minor variations in product typical test data are to be expected in normal manufacturing.

Rev: 05-Oct-2021